

APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

	-			•			
PRODUCT DAT	A SHEET (CONTRAC	TOR NAME: CAN	MSS Shelters			
1.PART NUMBER:	CAMSS40EX581	5G	2.NSN:				
		I.TYPE: Vel Shelter Sys	nicle Maintenance tem	5.CLASS:			
6.COLOR: 483 Olive Drab 7.		7. Support System: Frame		8.SERIES: CAMSS40EX			
9. INTENDED USE	E: Vehicle Mainten	ance Wareh	ouse, DFAC, Transit B	Billeting, UAV Support Shelter,			
10.DIMENSIONS (IN FEET AND INCHES)	LENGTH: 58'		WIDTH: 40'	HEIGHT: RIDGE/EAVE: 16'			
11.DIMENSIONS (EXTERNAL GUYED)	LENGTH: 58	,	WIDTH 52'				
12.SQUARE FEET							
2,320 Square Feet 13.WEIGHT			14.WEIGHT	15.SHIPPING CUBE			
(POUNDS, UNPACKAGED) 14,731 lbs			(PACKAGED) 16,131 lbs	(PACKAGED) 880 cu. ft			
16SHIPPING CONTAINER	LENGTH: 82		WIDTH: 96"	HEIGHT: 48" (4 Containers of this Size)			
17.SET-UP TIME/ NUMBER OF PERS	ONE 9 hours nor		18.STRIKE TIME/ NUMBER OF PERSON	IS. 4 hours/6 norsons			
cover system tensi- electric vertical lift	ons down onto th truss doors meas system. The elec	e shelter se uring 30' w	ecurely using a patent ide by 15' high, an ext	easier. The MIL SPEC double overlap ed pulley system. Optional items include treme temperature kit as well as a distribution panel, quick connect lighting			
20.DESCRIPTION: The CAMSS40EX58 Shelter System is in use throughout Afghanistan and Iraq for large vehicle maintenance shelters. The complete system is compact to ship (463L compatible), fast to erect (does not require heavy equipment), and provides a large working area with the optional electric vertical lift vehicle doors measuring 30' wide x 15' high. The vertical lift door option makes access in and out of the shelter quick and easy for large vehicles. The doors lift up vertically so they don't interfere with interior space and they don't leave an interior area exposed to weather as with baby buggy style doors.							
	PART NUMBER Or NSN	Included or Optional					
LIGHT SET	HIT-40EX5815-ELC	2 Optional	Complete electrical ki	t with 300amp 3phase distribution panel,			
Product Data Sheet			12 quick connect meta	al halide high bay lights, six 120v outlets, six			
Officer			220V outlets , and 400	DA power source cable.			
ELECTRICAL OUTLET SET Product Data Sheet							
FLOORING							

Product Data Sheet

HEATER

Product Data Sheet			
AIR			
CONDITIONER Broduct Data			
Product Data Sheet			
GENERATOR			
GENERATOR Product Data			
Sheet			
POWER DISTRIBUTION			
Product Data			
Sheet			
TRAILER			
MOUNTED			
SUPPORT			
SYSTEM Product Data Sheet			
	HIT-40EX5815-	Optional	Liner fabric is MIL-Spec and meets ASTM6413 fire resistance with
LINER Product Data Sheet	ETK01		a minimum weight of eight ounces per square yard. Internal
Data Sheet			liner system provides attic space. Includes four plenums.
INSULATED			
FLOORING Product Data			
Sheet			
SOLAR SHADE/			
CAMOU. NETT			
Product Data Sheet			
Container	LUT CCDO4	0	CANACC Community Companies
Container	HIT-CCR01	Optional	CAMSS Composite Container